



PM1500 BANDSAW

FEATURES

14 1/2" of throat and 14" of resaw provide more capacity than a traditional 14" bandsaw

Sturdy cast iron table and trunnion assembly offers maximum rigidity for heavy work pieces

Exclusive Powermatic T-Square style Accu-Fence maximizes accuracy and safety

The Accu-Fence has complete adjustability for aligning to blade and squaring to table

Positive locking cam with pressure adjustment

Oversized side plate can be used in the horizontal or vertical position

Solid steel resaw pin for optimum rigidity

Blade tension release with electrical interlock prevents the bandsaw from starting when the blade is de-tensioned or released

Heavy duty upper wheel support and tracking mechanism for smooth operation

Solid cast iron upper and lower wheels create the momentum needed for heavy resaw

High end blade guides with tool less adjustment provide stability, increasing cut accuracy

Price:



A | SIDE PLATE & CAM LOCK

Oversized side plate can be used in the horizontal or vertical position and positive locking cam with pressure adjustment

B | FOOT BRAKE

Integrated foot brake stops a coasting blade

C | TENSION RELEASE

Blade tension release with electrical interlock prevents the bandsaw from starting when the blade is de-tensioned or released





SPECIFICATIONS

Model Number	PM1500
Stock Number	1791500
Wheel Diameter (in.)	15
Cutting Capacity Width (in.)	14-1/2
Cutting Capacity Height (in.)	14
Blade Length (in.)	153
Blade Speed (SFPM)	3100
Table Dimension (LxW)	21-1/2 x 16
Blade Width (min-max/in.)	1/8-1
Table Height From Floor (in.)	40
Table Tilt	10 ° left, 45 ° right
Miter Gauge Positive Stops	45 °, 90 °
Dust Collection Minimum CFM	600
Dust Port Outer Diameter (in.)	4
Motor Power (hp)	3
Motor Phase (Ph)	1
Motor Voltage (V)	230
Prewired Voltage (V)	230
Motor Current (Amps)	12

★ ★ ★
POWERMATIC
 FACTORY DIRECT SHIP
 PROGRAM
 Ask your dealer
 for details.

5
 YEAR
 WARRANTY

THE POWERMATIC PROMISE



QUALITY



TECH SUPPORT



SERVICE PARTS

